

SLABACH ENTERPRISES Wheeler Reeler

Unleash your potential with our industry-leading reel trailers, built to withstand the toughest challenges and deliver unrivaled reliability. Experience the difference a Wheeler Reeler can make for your company today.

☎ 319-656-3434

✉ office@slabach.com

🌐 www.slabach.com

Hydraulic Rewind



- Re-spool cable with very little effort
- Easy adjustment to spool sizes
- Variable speed control
- Turns in either direction
- Hydraulic power pack available
- Mounts all Wheeler Reeler reel trailer models

I - 85



Payload Rating	8,500 lb.
Reel Diameter (max.)	120 in.
Reel Width (max.)	60 in.

I - 60



Payload Rating	6,000 lb.
Reel Diameter (max.)	120 in.
Reel Width (max.)	60 in.

45



Payload Rating	4,500 lb.
Reel Diameter (max.)	96 in.
Reel Width (max.)	54 in.

2 Spool
Bars

3 Spool
Bars



8' Max
Reel



MR120X2

Payload Rating	12,000 lb.
Reel Diameter (max.)	96 in.
Reel Width (max.)	60 in.
Trailer Length	19 ft.



MR120X3

Payload Rating	12,000 lb.
Reel Diameter (max.)	96 in.
Reel Width (max.)	60 in.
Trailer Length	26.5 ft.



10' Max
Reel



I-MR110X2

Payload Rating	11,000 lb.
Reel Diameter (max.)	120 in.
Reel Width (max.)	60 in.
Trailer Length	22.5 ft.



I-MR150X3

Payload Rating	15,000 lb.
Reel Diameter (max.)	120 in.
Reel Width (max.)	60 in.
Trailer Length	34 ft.